



GD 335

E-NR: 6332525

Glass Break Detector, Glued



The GD 335 is a glass break detector with transistor output that is connected to a control panel via an IU 300 interface unit. It is especially designed for monitoring shop windows, sliding glass doors, ordinary windows and other exposed glass surfaces, both in public spaces and private homes. It can be used on windows with protective film if the detector is mounted directly onto the glass and not on the film (a 5-10 cm hole must be cut out the film). It can also be used on glass cabinets to protect various types of equipment. The GD 335 glass break detector is activated when the glass is shattered or broken and is highly resistant to interference with the glass or in its immediate environment, which makes it ideal for 24-hour monitoring. Its circular design guarantees correct positioning. The GD 335 is glued to the glass pane and each detector is supplied with a stencil to mark the mounting location, a glue applicator and cable clamps for quick and easy installation.

For laminated glass please use GD 475.

ADDITIONAL INFORMATION

Longueur de câble (m)	3m, 6m, 10m
Zone de couverture max.	2 m radio (standard 3 mm glass)
Certifications	Class 2, EN 50131-2-7-2:2013 Grade 2, SBSC 10-32, VdS Klass B – G192532
Tension de l'alimentation	4-15 VDC
Consommation électrique	5 µA (7,5 mA alarm)
Sortie alarme	Transistor output
Indicateur d'alarme	LED
Température de fonctionnement	-40°C – +70°C
Indice de protection	IP 67
Dimensions (h x Ø) mm	11 x 27



Grade	2
Type de produit	Détecteurs
Environnement	Extérieur, Intérieur
Groupe de produits	Bris de glace
Caractéristique du produit	Collé, En surface
Domaine d'application	
Certification de sécurité et schémas d'agrément	EN, FG, SBSC, VdS
Classe de sécurité	2, B
Classe environnementale	IIIA

ORDER INFORMATION

Model	E-NR	Description
GD 335	6332525	
GD 335-6	6332526	
GD 335-10	6332527	

SCHEMATICS

