



3056

E-NR: 5010321

FUSE MODULE 10-30 V DC/AC

Terminal block for installation of alarm and access systems.

Tamper protected fuse module for spreading power supply 8 A to 4 sections.

Fuse module 3056 is designed for power distribution.

It contains a dual input for connection to power supply and four independently secured outputs. The normal state of each channel is signaled with green LEDs.

Errors detected in each channel (lack of voltage or activated fuse) is signaled by red LEDs and switching relay.

The terminal has screw connection with elevator function.

TECHNICAL DETAILS

Supply voltage	10-30 VDC, 8-20 VAC
Current consumption	22 mA @12 VDC, 32 mA @24 VDC
Tamper switch max. load	50 mA
Number of channels	4
Cable dimension - input	0,2 – 2,5 mm ²
Cable dimension - output	0,14 – 1,5 mm ²
Max. load per channel	30 V / 2 A
Input current max.	8 A
Dimensions (L x W)	116 x 40
Product type	Connection accessories
Environment	Indoor
Accessory type	Fuse board



Connection terminal	Fused
Terminal type	Screw/screw
Product line	Fatum
Product feature	Surface-mounted

ORDER INFORMATION

Model	E-NR	Description
3056.03	5010321	Fuse module, 10-30V DC/AC, Tamper Protected, Screw

SCHEMATICS

