




MC 270-S45

E-NR: 6332734

High Security Contact, NC



The MC 270-S45 set is intended for use in exposed environments where a more durable high security contact is needed, such as doors, gates, etc. The set consists of a contact part with NC contact function installed in MC 200-4 Al housing and an extra strong magnet in MC 200-5 Al housing, which allows for a wide opening gap. MC 270-S45 set contains a 1 m long stainless steel Flexi-tube protection (MC T4). Contact and magnet are paired. To ensure proper functionality, do not replace the contact or magnet alone.

TECHNICAL DETAILS

Approvals	Class 3/4,F&P, Class IIIA, EN 50131-2-6 Grade 3, NBÚ CZ Typ 3, NBÚ SK Typ 3, SBSC 9-205, VdS G 116028 Class C
Contact rating	48 VDC / 500 mA / 10 VA
Operating temperature	-40°C – +70°C
Housing protection class	IP 67
Make distance (wood) mm	34
Make distance (steel) mm	X
Housing material	Aluminium
Contact dimensions (L x W x H) mm	74 x 25 x 15
Magnet dimensions (L x Ø) mm	74 x 25 x 15
Sabotage distance (wood) mm	20
Normal operation	12 VDC
Grade	3
Product type	Detectors
Environment	Indoor
Product group	Magnetic contact
Product feature	Surface-mounted
Application area	



Security certification and approval schemes	EN, F&P, NBU, SBSC, VdS
Security class	3, C
Environmental class	IIIA

ORDER INFORMATION

Model	E-NR	Description
MC 270-S45	6332734	High security contact set, NC, 6 m cable

SCHEMATICS

