



MC 340

E-NR: 6332760

Magnetic Contact, Recessed mounting, NC



MC 340 is a universal magnetic contact with NC function that can be used in both alarm and access control systems for monitoring e.g. doors and windows against unauthorized opening. Both the contact and the magnet part are encased in a water proof (IP67) plastic housing, which enables easy installation into wood without additional accessories. With our extensive range of installation accessories it is easy to install the contact either recessed or as a surface mount on metal and other materials.

TECHNICAL DETAILS

Cable length	2m, 5m, 10m
Approvals	Class 1/2,FG, Class IIIA, CNPP 2124030002A0, EN 50131-2-6 Grade 2, GRADE 2 + RTC, INCERT B-582-1003, NBÚ CZ Typ 2,NBÚ SK Typ 2,NF&A2P, SBSC 9-200, VdS G 196670 Class B
Contact rating	48 VDC / 500 mA / 10 VA
Operating temperature	-40°C – +70°C
Housing protection class	IP 67
Drill diameter mm	8
Make distance (wood) mm	21
Make distance (steel) mm	X
Contact dimensions (L x Ø) mm	26 x 9
Magnet dimensions (L x Ø) mm	26 x 9
Grade	2
Product type	Detectors
Environment	Indoor
Product group	Magnetic contact



Product feature

Flush-mounted

Application area

Security certification and approval schemes

EN, F&P, FG, INCERT, NBU, NF&A2P, SBSC, VdS

Security class

2, B

Environmental class

IIIA

ORDER INFORMATION

Model	E-NR	Description
MC 340	6332760	Recessed magnetic contact, NC, 2 m cable
MC 340-5	6332761	Recessed magnetic contact, NC, 5 m cable
MC 340-10	6332762	Recessed magnetic contact, NC, 10 m cable
MC 340-C	6332763	Recessed contact without magnet, NC, 5 m cable
MC 340-BL		Recessed magnetic contact, NC, 2 m cable, black
MC 340-5BL		Recessed magnetic contact, NC, 5 m cable, black
MC 340-10BL		Recessed magnetic contact, NC, 10 m cable, black
MC 340-CBL		Recessed contact without magnet, NC, 5 m cable, black

SCHEMATICS

