



RM 12

E-NR: 6332880

Indicator-/relay module

The RM 12 is a monitoring module that can be used as an annunciator to monitor, for example, door status or as a relay module that converts OC outputs to relay outputs with an alternating function.

The relay module RM 12 consists of 12 independent, parallel inputs with pull-up resistor and relay outputs (alternating NO/NC) that follow input status. The inputs can be driven directly from OC outputs with extra resistors or accessories. The output relays follow input status and the relay is active when input is connected to earth. Each channel is separately indicated via a LED on the front panel.

The unit also has a summary alarm function for all 12 inputs. The summary alarm is indicated via a separate LED indicator and on a separate relay output (alternating NO/NC).

The unit has two jumper blocks with the option of choosing whether the LED and summary alarm are latched until reset or self-reset mode. There is also the option of choosing if the buzzer is active when the summary alarm relay is activated or whether the buzzer should remain disconnected.

TECHNICAL DETAILS

Contact rating	30 VDC / 1 A
Product type	Connection accessories
Environment	Indoor
Dimensions (L x W x H) mm	180 x 110 x 43
Relay output	12 + 1, NC/NO
Accessory type	Module series (Empty)
Product feature	Surface-mounted



ORDER INFORMATION

Model	E-NR	Description
RM 12	6332880	

